

**CORDIAM srl**

Via Madonna, 19


22070 Guanzate (CO) - Italia-

Tel +39 031 97 72 74 - Fax +39 031 97 66 15

e-mail: info@cordiam.it - www.cordiam.it

T4-300-EL

DATI TECNICI - PERFORMANCE DATA
TECHNISCHE DATEN - EN DONNÉES TECHNIQUES
TEKNISKE DATA - DATOS TECNICOS

**TENSIONE** - Voltage - Spannung - Spænding - Tension - Tension**V** 230 (220 - 240) 120 (110 - 115)**CORRENTE DI TARGA** - Nameplate Amps.-Stromaufnahme - Amp. - Ampérage - Corriente de carga**A** 16 25**POTENZA DI TARGA** - Nameplate Power - Leistungsaufnahme - Watterfekt - Puissance entrée - Potencia de carga**W** 3420 2820**FREQUENZA** - Frequency - Frekvens - Frequenz - Fréquence - Frecuencia**Hz** 50 ÷ 60 50 ÷ 60**GIRI A VUOTO** - No-load RPM - Leerlaufdrehzal - Omdrejninger uberlastede - Vitesse à vide - R.P.M. en vacío**min⁻¹** 490 ÷ 1160 440 ÷ 1030**GIRI A CARICO** - Full-load RPM - Lastdrehzahl - Omdrejninger belastade - Vitesse en charge - R.P.M. en carga**min⁻¹** 320 ÷ 760 290 ÷ 680**POTENZA DI RESA** - Output power - Leistungsabgabe - Afgivende effekt - Puissance sortie - Potencia de salida**W** 2220 1850**COPPIA (a 2220 - 1850W)** - Torque - Drehmoment - Moment - Couple - Par**Nm** 65 ÷ 28 60 ÷ 26**GAMMA DI FORATURA** - Drilling Range - Bohrkronen - Borstorrelser - Capacité de forage - Gamma de perforacion**mm** 50 ÷ 300 50 ÷ 300**PESO** - Weight - Gewicht - Vægt - Poids - Peso**Kg** 12,5 12,5**Avviamento lento-limitatore di punto** - Soft start - Sanftanlauf und Anlaufstrombegrenzer- Mise on route progressive - Arranque suave

electronic

electronic

Frizione elettronica - Electronic clutch - Überlastungsbegrenzer- - Embrayage electronic - embrague eletrónico

electronic

electronic

ATTACCO CORONA - Bit connection - Bohrkronenanschulss - Adapter - Raccord - Acoplamiento de corona

1" 1/4 UNC

1" 1/4 UNC

COPPIA DI TARATURA FRIZIONE - Clutch torque - Drehmoment der Rurschkupplung - Couple de friction - Justeringsnogle til kobling - Koppelingsinstellung**Nm** 60 45**QUANTITA' E TIPO D' OLIO** - Quantity and type of oil - Menge und typ des Öls - Quantité et type de huile - Mænde og type af olie - Smerclie type en hoeveelheid - Cantidad y tipo de aceiteE.P.68+150cST
(ex. ESSO Spartan E.P.68; ESSO Spartan E.P.150)**g** 300 300**QUANTITA' E TIPO DI GRASSO** -Quantity and type of grease - Menge und typ des fett - Quantité et type de graisse - Mængde og type af fedt

LUBCON THERMOPLEX ALN 250I00 EP

g 25 25**FRIZIONE MECCANICA IN BRONZO** - CLUTCH SYSTEM WITH BRASS RINGS - SICHERHEITSKUPPLUNG MIT BRONZESCHEIBEN - SYSTEME D'EMBAYAGE AVEC BAGUES LAITONNÉES - SLIPKOPPELING MET BRONZEN RINGEN - KOBLINGSSYSTEM MED BRONZESKIVER - SISTEMA DE EMBRAGUE CON ANILLOS DE BRONCE