

**CORDIAM srl**



Via Madonna, 19

22070 Guanzate (CO) - Italia-

Tel +39 031 97 72 74 - Fax +39 031 97 66 15

e-mail: info@cordiam.it - www.cordiam.it

**TO MU-EL
T1750 N EL****DATI TECNICI - PERFORMANCE DATA - TECHNISCHE DATEN - EN DONNÉES
TECHNIQUES - TEKNISKE - DATA - DATOS TECNICOS**

TENSIONE - Voltage - Spannung - Spænding-Tension - Tension	V	230 (220 - 240)	115 (110 - 120)
CORRENTE DI TARGA - Nameplate Amps.-Stromaufnahme - Amp. - Ampérage - Corriente de carga	A	8	15
POTENZA DI TARGA - Nameplate Power - Leistungsaufnahme - Watterffekt - Puissance entrée - Potencia de carga	W	1750	1700
FREQUENZA - Frequency - Frekvens - Frequenz - Fréquence - Frecuencia	Hz	50 - 60	50 - 60
GIRI A VUOTO - No-load RPM - Leerlaufdrehzal - Omdrejninger uberlastede - Vitesse à vide - R.P.M. en vacío	min ⁻¹	2180 - 4000	2250 - 4100
GIRI A CARICO - Full-load RPM - Lastdrehzahl - Omdrejninger belastade - Vitesse en charge - R.P.M. en carga	min ⁻¹	1470 - 2690	1780 - 3260
POTENZA DI RESA - Output power - Leistungsabgabe - Afgivende effekt - Puissance sortie - Potencia de salida	W	1155	1120
COPPIA (a 1220 - 1120 W) - Torque - Drehmoment - Moment - Couple - Par	Nm	8 - 4	6 - 3
Avviamento lento-limitatore di spunto - Soft start - Sanftanlauf und Anlaufstrombegrenzer- Mise on route progressive - Arranque suave		electronic	electronic
Frizione elettronica - Electronic clutch - Überlastungsbegrenzer- - Embrayage electronic - embrague eletrónico		electronic	electronic
GAMMA DI FORATURA - Drilling Range - Bohrkronen - Borstorrelser - Capacité de forage - Gamma de perforacion		15 - 127	15 - 127
		15 - 70	10 - 52
PESO - Weight - Gewicht - Vægt - Poids - Peso	Kg	5,5	5,5
ATTACCO CORONA - Bit connection - Bohrkronenanschulss - Adapter - Raccord - Acoplamiento de corona		1/2 GAS	1/2 GAS
QUANTITA' E TIPO D' OLIO - Quantity and type of oil - Menge und typ des Öls - Quantité et type de huile - Mængde og type af olie - Smerclie type en hoeveelheid - Cantidad y tipo de aceite		P.68+150cST (ex. ESSO Spartan E.P.68;ESSO Spartan E.P.15)	
	g	70	70
COPPIA DI TARATURA FRIZIONE - Clutch torque - Drehmoment der Rurschkupplung - Couple de friction - Justeringsnogle til kobling - Koppelingsinstelling	Nm	3,5	3,5
QUANTITA' E TIPO DI GRASSO -Quantity and type of grease - Menge und typ des fett - Quantité et type de graisse - Mængde og type af fedt		LUBCON THERMOPLEX ALN 250/00 EP	
	g	20	20

FRIZIONE MECCANICA IN BRONZO - CLUTCH SYSTEM WITH BRASS RINGS - SICHERHEITSKUPPLUNG MIT BRONZESCHEIBEN - SYSTEME D'EMBRAYAGE AVEC BAGUES LAITONNÉES - SLIPKOPPELING MET BRONZEN RINGEN - KOBLINGSSYSTEM MED BRONZESKIVER - SISTEMA DE EMBRAGUE CON ANILLOS DE BRONCE

